## NSN 5950-00-995-4733

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-995-4733

Reliability Indicator:
Not established
Overall Length:
14.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
9.500 inches single mounting facility single center group
Mounting Hole Diameter:
0.340 inches single group and 0.353 inches single group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Length:
11.750 inches
Body Width:
10.250 inches
Body Height:
7.500 inches
Maximum Operating Temp:
105.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
8 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
3 primary single component and 1 secondary single component
Winding Operating Current:
195.0 milliamperes ac single component single secondary and 340.0 milliamperes ac single component single secondary
Winding Operating Voltage:
440.00 ac pounds per hour wet single component all primary
Terminal Type And Quantity:
3 standoff, threaded stud and 6 threaded stud
Specification Or Standard:
Tf4rx02yy type
Shelf Life:
N/a

## NSN 5950-00-995-4733

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

