

View Online at <https://aerobasegroup.com/nsn/5950-00-997-3340>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

75.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.000 inches

Body Width:

1.000 inches

Body Height:

1.125 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

100.0 milliamperes dc single component single secondary

Winding Operating Voltage:

45.00 ac volts single component single secondary and 75.00 ac volts single component single secondary and 115.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0