

View Online at <https://aerobasegroup.com/nsn/5950-00-998-5229>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches single mounting facility single center group

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

50.0 hertz single component and 500.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.750 inches

Body Width:

3.125 inches

Body Height:

3.250 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

2.0 amperes ac single component all secondary

Winding Operating Voltage:

5.00 ac volts single component 1st secondary or 10.00 ac volts single component 1st secondary or 20.00 ac volts single component 1st secondary or 30.00 ac volts single component 1st secondary or 40.00 ac volts single component 1st secondary or 50.00 ac volts single component 1st secondary

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0