

View Online at <https://aerobasegroup.com/nsn/5950-01-004-7246>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.940 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 62.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

7.250 inches

Body Width:

6.250 inches

Body Height:

5.190 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

20.0 amperes ac single component single secondary

Winding Power Rating:

960.0 volts-amperes single component single secondary

Winding Operating Voltage:

48.00 ac volts single component single secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0