## NSN 5950-01-004-7256

Radio Frequency Coil - Page 1 of 1



View Online at https://aerobas

| View Online at https://aerobasegroup.com/nsn/5950-01-004-7256   |
|---|
| Reliability Indicator:  |
| Not established   |
| Inductance Rating:  |
| 120.00 microhenries single component single winding   |
| Coil Form Type:   |
| Solid single component  |
| Body Length:  |
| Between 0.875 inches and 1.000 inches   |
| Body Outside Diameter:  |
| Between 0.250 inches and 0.313 inches   |
| Maximum Operating Temp:   |
| 105.0 degrees celsius   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Terminal single group   |
| Rating Method:  |
| Electrical single component single winding  |
| Winding Conductor Size:   |
| 0.02846 inches american wire gage single component single winding   |
| Winding Operating Current:  |
| 195.0 milliamperes dc single component single winding   |
| Dc Resistance Rating In Ohms:   |
| 4.100 single component single winding   |
| Quality Factor:   |
| 95 single component single winding  |
| Test Data Document:   |
| 8134915305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental       |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Terminal Type And Quantity:   |
| 2 wire lead   |
| Specification Data:   |
| 96906-ms75103 government standard   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiia:   |

Mil-prf-15305 spec.

Mil-std (military Standard):

A058b0