

View Online at <https://aerobasegroup.com/nsn/5950-01-006-7850>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.688 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 4.187 inches and 4.312 inches

Body Width:

Between 3.563 inches and 3.688 inches

Body Height:

Between 5.374 inches and 5.562 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

1.8 amperes ac single component 4th secondary

Winding Operating Voltage:

50.00 ac volts single component 1st secondary

Special Features:

Six secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0