

View Online at <https://aerobasegroup.com/nsn/5950-01-006-7859>

Reliability Indicator:

Not established

Inductance Rating:

16.00 millihenries single component all secondary

Frequency Rating:

4.8 megahertz single component

Coil Form Type:

Solid single component

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component and core grounded and brought out to terminal single component

Body Length:

Between 1.720 inches and 1.780 inches

Body Width:

Between 1.720 inches and 1.780 inches

Body Height:

Between 2.630 inches and 2.870 inches

Distance Between Mounting Facility Centers:

1.480 inches single mounting facility single center group and 1.520 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component all primary

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Features Provided:

Color coded lead

Thread Size:

0.138 inches single group

Winding Conductor Size:

0.01264 inches american wire gage single component all secondary

Special Features:

Primary shield is brought out to primary terminal; secondary shield is brought out to secondary terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0