## NSN 5950-01-006-8281

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-006-8281

Iot established Overall Length: .687 inches Center To Center Distance Between Mounting Facilities Parallel To Length: .188 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: .188 inches single mounting facility single center group Frequency Rating: 5.0 hertz single component and 400.0 hertz single component hput-output Phase Relationship: Single phase to single phase single component Vinding Shielding Method: hternal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches Body Height: .250 inches
.687 inches Center To Center Distance Between Mounting Facilities Parallel To Length: .188 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: .188 inches single mounting facility single center group Frequency Rating: 5.0 hertz single component and 400.0 hertz single component hput-output Phase Relationship: Single phase to single phase single component Vinding Shielding Method: hternal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches
.687 inches Center To Center Distance Between Mounting Facilities Parallel To Length: .188 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: .188 inches single mounting facility single center group Frequency Rating: 5.0 hertz single component and 400.0 hertz single component hput-output Phase Relationship: Single phase to single phase single component Vinding Shielding Method: hternal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches
.188 inches single mounting facility single center group <b>Center To Center Distance Between Mounting Facilities Parallel To Width:</b> .188 inches single mounting facility single center group <b>Frequency Rating:</b> 5.0 hertz single component and 400.0 hertz single component <b>hput-output Phase Relationship:</b> Single phase to single phase single component <b>Vinding Shielding Method:</b> hternal shield grounded to core single component <b>Sody Length:</b> .625 inches <b>Body Width:</b> .625 inches <b>Body Height:</b>
.188 inches single mounting facility single center group <b>Center To Center Distance Between Mounting Facilities Parallel To Width:</b> .188 inches single mounting facility single center group <b>Frequency Rating:</b> 5.0 hertz single component and 400.0 hertz single component <b>hput-output Phase Relationship:</b> Single phase to single phase single component <b>Vinding Shielding Method:</b> hternal shield grounded to core single component <b>Sody Length:</b> .625 inches <b>Body Width:</b> .625 inches <b>Body Height:</b>
Center To Center Distance Between Mounting Facilities Parallel To Width: .188 inches single mounting facility single center group frequency Rating: 5.0 hertz single component and 400.0 hertz single component hput-output Phase Relationship: Single phase to single phase single component Vinding Shielding Method: Internal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches
Frequency Rating: 5.0 hertz single component and 400.0 hertz single component hput-output Phase Relationship: Single phase to single phase single component Vinding Shielding Method: hternal shield grounded to core single component Sody Length: .625 inches Sody Width: .625 inches Sody Height:
5.0 hertz single component and 400.0 hertz single component hput-output Phase Relationship: Single phase to single phase single component Vinding Shielding Method: hternal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches Body Height:
Anput-output Phase Relationship: Single phase to single phase single component Vinding Shielding Method: Internal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches Body Height:
Anput-output Phase Relationship: Single phase to single phase single component Vinding Shielding Method: Internal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches Body Height:
Single phase to single phase single component Vinding Shielding Method: Internal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches Body Height:
Vinding Shielding Method: Internal shield grounded to core single component Body Length: .625 inches Body Width: .625 inches Body Height:
nternal shield grounded to core single component <b>Body Length:</b> .625 inches <b>Body Width:</b> .625 inches <b>Body Height:</b>
Body Length:         .625 inches         Body Width:         .625 inches         Body Height:
.625 inches Body Width: .625 inches Body Height:
.625 inches Body Height:
Body Height:
.250 inches
nclosure Type:
lermetically sealed
Iounting Facility Quantity:
single group
Jounting Method:
hreaded stud single group
Vinding Function And Quantity:
primary single component and 1 secondary single component
hready Qty Per Inch (tpi):
2 single group
hread Size:
.138 inches single group
Vinding Operating Current:
00.0 milliamperes ac single component single secondary
Vinding Operating Voltage:
8.50 ac volts single component single secondary
hread Series Designator:
Inc single group
erminal Type And Quantity:
wire hook
Shelf Life:
I/a

## NSN 5950-01-006-8281

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

