

View Online at <https://aerobasegroup.com/nsn/5950-01-006-8605>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.000 inches

Body Width:

2.000 inches

Body Height:

1.250 inches

End Application:

Nimitz class cvn, wasp class lhd, oliver perry class ffg, arleigh burke burke class ddg, sturgeon class ssn (637), ticonderoga class cg (47), austin ship class lpd-4 amphibious transport docks, los angeles class ssn (688), forrestal class cv, spruance class dd (963)

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Criticality Code Justification:

Feat

Winding Operating Voltage:

3.00 ac volts single component single primary input

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

24 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0