## NSN 5950-01-007-1792

Power Transformer - Page 1 of 1

A058b0



View Online at https://aerobasegroup.com/nsn/5950-01-007-1792

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.125 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.375 inches single mounting facility single center group
Mounting Hole Diameter:
0.188 inches single group
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
3.938 inches
Body Width:
3.250 inches
Body Height:
3.375 inches
End Application:
Coliver perry class ffg, virginia class cgn (41), arleigh burke class ddg, spruance class dd (963), nimitz class cvn, kidd class ddg,
ticonderoga class cg (47), forrestal class cv, wasp class lhd.
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
2 primary single component and 2 secondary single component
Criticality Code Justification:
Feat
Winding Operating Voltage:
120.00 ac pounds per hour wet single component all primary
Special Features:
Weapon system essential
Terminal Type And Quantity:
8 wire lead
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: