

View Online at <https://aerobasegroup.com/nsn/5950-01-007-1792>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.938 inches

Body Width:

3.250 inches

Body Height:

3.375 inches

End Application:

Coliver perry class ffg, virginia class cgn (41), arleigh burke class ddg, spruance class dd (963), nimitz class cvn, kidd class ddg, ticonderoga class cg (47), forrestal class cv, wasp class lhd.

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Criticality Code Justification:

Feat

Winding Operating Voltage:

120.00 ac pounds per hour wet single component all primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0