NSN 5950-01-008-3155

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-008-3155

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.188 inches single mounting facility single center group
Mounting Slot Width:
0.156 inches single group
Inductance Type:
Fixed
Inductance Rating:
50.00 millihenries single component single winding
Frequency Rating:
50.0 hertz single component and 60.0 hertz single component
Body Length:
2.375 inches
Body Width:
2.250 inches
Body Height:
2.875 inches
End Application:
Medium intensity approach lighting system, fa8767 (mals)
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and slot single group
Winding Operating Current:
4.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
10.000 single component single winding
Special Features:
L-201, ti6850.9, instruction bk, malsr, pg 8-15, gte sylvania
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-01-008-3155

Reactor - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0