

View Online at <https://aerobasegroup.com/nsn/5950-01-008-5450>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.870 inches

Body Width:

2.620 inches

Body Height:

3.450 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

6.0 amperes ac single component single secondary

Winding Power Rating:

51.0 volts-amperes single component single secondary

Winding Operating Voltage:

8.50 ac pounds per hour wet single component single secondary

Special Features:

To be operated immersed in oil

Terminal Type And Quantity:

2 tab, solder lug and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0