## NSN 5950-01-009-9864

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-009-9864

| Reliability Indicator:   |
|--|
| Not established  |
| Inductance Rating:   |
| 8.20 microamperes finished-chamfered single component single winding   |
| Coil Form Type:  |
| Solid single component   |
| Core Construction:   |
| Solid single component   |
| Body Length:   |
| Between 0.365 inches and 0.385 inches  |
| Overall Diameter:  |
| 0.146 mils and 0.166 centimeters   |
| Maximum Operating Temp:  |
| 105.0 degrees celsius  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Terminal single group  |
| Rating Method:   |
| Electrical single component single winding   |
| Winding Conductor Size:  |
| 0.02535 inches american wire gage single component single winding  |
| Winding Operating Current:   |
| 360.0 milliamperes dc single component single winding  |
| Dc Resistance Rating In Ohms:  |
| 0.600 single component single winding  |
| Quality Factor:  |
| 50 single component single winding   |
| Test Data Document:  |
| 81349-mil-prf-15305 specification specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in |
| specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on      |
| certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                      |
| Terminal Type And Quantity:  |
| 2 wire lead  |
| Specification Data:  |
| 96906-ms14046 government standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |

Fiig: A058b0

## NSN 5950-01-009-9864

Radio Frequency Coil - Page 2 of 2



Mil-std (military Standard):

Mil-prf-15305 spec.