

View Online at <https://aerobasegroup.com/nsn/5950-01-011-3414>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.140 inches

Body Width:

3.140 inches

Body Height:

3.770 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

100.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

5.4 volts-amperes single component 2nd secondary

Winding Operating Voltage:

54.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0