

View Online at <https://aerobasegroup.com/nsn/5950-01-011-5252>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.906 inches single mounting facility single center group

Overall Height:

3.940 inches

Frequency Rating:

60.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.656 inches

Body Width:

1.360 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

600.0 microamperes dc single component all primary

Winding Operating Voltage:

90.00 ac volts single component all primary

Special Features:

2 of 1st primary leads split, attached to a resistor each, and brought out to terminals

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0