

View Online at <https://aerobasegroup.com/nsn/5950-01-011-5348>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.210 inches single mounting facility single center group and 1.270 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.780 inches single mounting facility single center group and 0.840 inches single mounting facility single center group

Overall Width:

1.710 inches

Mounting Hole Diameter:

0.178 inches single group and 0.198 inches single group

Frequency Rating:

4.0 kilohertz single component and 5.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 1.590 inches and 1.710 inches

Body Height:

Between 1.220 inches and 1.280 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

100.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

53.03 ac volts single component single primary

Test Data Document:

06401-7904518 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0