

View Online at <https://aerobasegroup.com/nsn/5950-01-013-0262>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.687 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.437 inches single mounting facility single center group

**Frequency Rating:**

47.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

2.312 inches

**Body Width:**

2.062 inches

**Body Height:**

3.312 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

250.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

4.00 ac volts single component single secondary and 4.20 ac volts single component single secondary and 4.60 ac volts single component single secondary and 4.80 ac volts single component single secondary and 5.00 ac volts single component single secondary and 5.20 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0