

View Online at <https://aerobasegroup.com/nsn/5950-01-014-2968>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.630 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

50.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

5.750 inches

Body Width:

4.500 inches

Body Height:

5.330 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Voltage:

26.00 ac volts single component single secondary and 30.00 ac volts single component single secondary and 36.00 ac volts single component single secondary and 72.00 ac volts single component single secondary and 98.00 ac volts single component single secondary

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0