

View Online at <https://aerobasegroup.com/nsn/5950-01-014-4873>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.182 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.625 inches

Body Width:

2.593 inches

Body Height:

3.125 inches

Distance Between Mounting Facility Centers:

3.125 inches single mounting facility single center group

End Application:

Wsd: missile system, aegis surface (sms) mk 7; wasp class lhd; forrestal cv; ticonderoga cg (47); arleigh burke ddg; blue ridge lcc-19

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

15.0 milliamperes ac single component single winding

Criticality Code Justification:

Feat

Winding Operating Voltage:

6.30 ac pounds per hour wet single component 1st secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0