NSN 5950-01-015-8357

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-015-8357

| view Offiline at https://aerobasegroup.com/hist//0350-01-010-000/ |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.500 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core and brought out to terminal single component |
| Body Length: |
| 4.000 inches |
| Body Width: |
| 3.000 inches |
| Body Height: |
| 4.250 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Strap single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 37.0 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 6.60 ac pounds per hour wet single component single secondary |
| Terminal Type And Quantity: |
| 7 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

A058b0