

View Online at <https://aerobasegroup.com/nsn/5950-01-015-8364>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.125 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.030 inches

Body Width:

1.750 inches

Body Height:

2.380 inches

Maximum Operating Temp:

70.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

7.0 milliamperes dc single component single secondary

Winding Operating Voltage:

620.00 dc volts single component single secondary or 670.00 dc volts single component single secondary or 790.00 dc volts single component single secondary or 860.00 dc volts single component single secondary or 990.00 dc volts single component single secondary or 1080.00 dc volts single component single secondary

Special Features:

Secondary voltages taken after bridge rectifier on the out-put; current also taken from same location

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0