

View Online at <https://aerobasegroup.com/nsn/5950-01-017-0762>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.688 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.562 inches

Body Width:

3.938 inches

Body Height:

5.812 inches

Maximum Operating Temp:

70.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

500.0 milliamperes dc single component 3rd secondary

Winding Operating Voltage:

81.30 ac volts single component single primary

Special Features:

1 primary winding; 5 secondary windings; dc current has been rectified

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

18 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0