

View Online at <https://aerobasegroup.com/nsn/5950-01-017-0763>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.688 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

7.000 inches

Body Width:

4.750 inches

Body Height:

5.812 inches

Maximum Operating Temp:

70.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Features Provided:

W/rectifier

Thread Size:

0.250 inches single group

Winding Operating Current:

3.0 amperes dc single component 2nd secondary

Winding Operating Voltage:

22.50 ac volts single component 2nd secondary

Special Features:

1primary winding; 7secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

24 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0