

View Online at <https://aerobasegroup.com/nsn/5950-01-017-2052>

Reliability Indicator:

Not established

Impedance Rating In Ohms:

1000.0 all components single secondary

Frequency Rating:

1.0 kilohertz all components and 100.0 kilohertz all components

Input-output Phase Relationship:

Single phase to single phase all components

Winding Shielding Method:

Internal shield brought out to terminal all components

Body Length:

Between 1.969 inches and 2.031 inches

Body Width:

Between 0.969 inches and 1.031 inches

Body Height:

Between 0.469 inches and 0.531 inches

Maximum Operating Temp:

105.0 degrees celsius

Distance Between Mounting Facility Centers:

0.969 inches single mounting facility single center group and 1.031 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical all components single secondary

Winding Function And Quantity:

1 primary all components and 1 secondary all components

Thread Size:

0.112 inches single group

Winding Operating Voltage:

3.09 ac volts all components single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0