

View Online at <https://aerobasegroup.com/nsn/5950-01-017-3044>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.688 inches

Body Width:

4.125 inches

Body Height:

5.250 inches

End Application:

Instrument landing system, fa9350-9399 (mark1d)

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

8.0 amperes ac single component single secondary

Winding Power Rating:

248.0 volts-amperes single component single secondary

Winding Operating Voltage:

31.00 ac pounds per hour wet single component single secondary

Special Features:

Function, transformer, power, step-down; reference data, 7t1, ti-6750.80, fa 9354, pg 8-11; 7t1, ti-6750.100, fa 9707, pg 8-7; 7t1, ti-6750.152, fa 9911, pg 8-13

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0