

View Online at <https://aerobasegroup.com/nsn/5950-01-018-3073>

**Reliability Indicator:**

Not established

**Turn Quantity:**

3900 single component single winding

**Frequency Rating:**

60.0 hertz single component

**Core Construction:**

Powdered single component

**Body Length:**

1.375 inches

**Body Outside Diameter:**

1.625 inches

**End Application:**

Wsd: fire pumps; nimitz class cvn; forrestal cv; oliver perry ffg; ticonderoga cg (47); virginia cgn (41); arleigh burke ddg; spruance dd (963); kidd ddg

**Winding Quantity:**

1 single component

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Rating Method:**

Electrical single component single winding and winding turns single component single winding

**Winding Conductor Size:**

0.00893 inches american wire gage single component single winding

**Winding Operating Current:**

20.0 milliamperes dc single component single winding

**Dc Resistance Rating In Ohms:**

224.500 single component single winding

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

115.00 dc pounds per hour wet single component single winding

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0