

View Online at <https://aerobasegroup.com/nsn/5950-01-019-6037>

Reliability Indicator:

Not established

Overall Length:

Between 7.410 inches and 7.470 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.615 inches single mounting facility single center group and 5.635 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.865 inches single mounting facility single center group and 1.885 inches single mounting facility single center group

Overall Height:

Between 7.070 inches and 7.130 inches

Overall Width:

Between 2.870 inches and 2.930 inches

Mounting Hole Diameter:

0.214 inches single group and 0.224 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Maximum Transformer Power Rating:

2100.0 watts single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.5 amperes ac single component single primary

Winding Operating Voltage:

200.00 ac volts single component single primary

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0