

View Online at <https://aerobasegroup.com/nsn/5950-01-021-4636>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.062 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.312 inches single mounting facility single center group

**Frequency Rating:**

57.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

5.000 inches

**Body Width:**

4.250 inches

**Body Height:**

6.750 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 7 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

100.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

80.00 ac volts single component 1st secondary

**Special Features:**

7secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0