## NSN 5950-01-022-0612

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-022-0612

Reliability Indicator:
Not established
Turn Quantity:
1933 single component single winding
Mounting Hole Diameter:
0.700 inches single group
Core Construction:
S0lid single component
Body Length:
2.469 inches
Body Outside Diameter:
1.350 inches
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Winding Conductor Size:
0.01594 inches american wire gage single component single winding
0.01594 inches american wire gage single component single winding  Winding Operating Current:
Winding Operating Current:
Winding Operating Current:  1.14 amperes dc single component single winding
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:  28.00 dc pounds per hour wet single component single winding
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:  28.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:  28.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 tab, solder lug
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:  28.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:  28.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:  28.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:  28.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:
Winding Operating Current:  1.14 amperes dc single component single winding  Dc Resistance Rating In Ohms:  21.000 single component single winding  Winding Operating Voltage:  28.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: