

View Online at <https://aerobasegroup.com/nsn/5950-01-022-6580>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 2.687 inches and 2.750 inches

Body Width:

Between 2.312 inches and 2.375 inches

Body Height:

Between 3.624 inches and 3.812 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed with oil

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

500.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

9.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0