

View Online at <https://aerobasegroup.com/nsn/5950-01-023-3234>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration proof

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.279 inches single group and 0.286 inches single group

Frequency Rating:

57.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

6.250 inches

Body Width:

3.500 inches

Body Height:

7.120 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

75.0 amperes ac single component single secondary

Winding Operating Voltage:

7.50 ac volts single component single secondary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0