## NSN 5950-01-023-3234

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-023-3234

| Reliability Indicator:  |
|---|
| Not established   |
| Hazardous Locations/environmental Protection:                             |
| Vibration proof   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 5.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.500 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.279 inches single group and 0.286 inches single group                   |
| Frequency Rating:   |
| 57.0 hertz single component and 440.0 hertz single component              |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to core single component                         |
| Body Length:  |
| 6.250 inches  |
| Body Width:   |
| 3.500 inches  |
| Body Height:  |
| 7.120 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Unthreaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Winding Operating Current:  |
| 75.0 amperes ac single component single secondary                         |
| Winding Operating Voltage:  |
| 7.50 ac volts single component single secondary                           |
| Terminal Type And Quantity:   |
| 5 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

## NSN 5950-01-023-3234

Power Transformer - Page 2 of 2

**Fiig:** A058b0

