NSN 5950-01-023-4992

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-023-4992

_			
R۵	liahi	litv	Indicator:
ĸe	IIabi	IILV	mulcator.

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant and vibration resistant

Overall Length:

1.730 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.405 inches single mounting facility single center group and 1.435 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.405 inches single mounting facility single center group and 1.435 inches single mounting facility single center group

Overall Height:

2.110 inches

Overall Width:

1.730 inches

Frequency Rating:

26.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

3.0 amperes dc single component single secondary

Winding Operating Voltage:

70.70 ac volts single component single primary

Special Features:

Secondary current is rectified

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

NSN 5950-01-023-4992

Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0