# NSN 5950-01-023-4992

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-023-4992

| _  |       |      |            |
|----|-------|------|------------|
| R۵ | liahi | litv | Indicator: |
| ĸe | IIabi | IILV | mulcator.  |

Not established

#### **Hazardous Locations/environmental Protection:**

Fungus resistant and moisture resistant and vibration resistant

## **Overall Length:**

1.730 inches

#### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.405 inches single mounting facility single center group and 1.435 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.405 inches single mounting facility single center group and 1.435 inches single mounting facility single center group

#### **Overall Height:**

2.110 inches

#### **Overall Width:**

1.730 inches

#### Frequency Rating:

26.0 kilohertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

# **Maximum Operating Temp:**

155.0 degrees celsius

# Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### **Thread Size:**

0.112 inches single group

# **Winding Operating Current:**

3.0 amperes dc single component single secondary

## **Winding Operating Voltage:**

70.70 ac volts single component single primary

#### **Special Features:**

Secondary current is rectified

# **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

5 turret

# Shelf Life:

N/a

# NSN 5950-01-023-4992

Power Transformer - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0