Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-023-5474

Reliability indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 4.000 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Mounting Hole Diameter: 0.437 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Method: Flange single group and unthreaded hole single group Winding Method: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 12.0.0 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:
Center To Center Distance Between Mounting Facilities Parallel To Length: 4.000 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Mounting Hole Diameter: 0.437 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Nuf
 4.000 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Mounting Hole Diameter: 0.437 inches single group Frequency Rating: 60.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group and unthreaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Terminal Type And Quantity: 3 tab, solder lug Net Life: N/a
Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Mounting Hole Diameter: 0.437 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Method: Flange single group and unthreaded hole single group Mounting Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Voltage: 120.00 ac volts single component single primary output Minding Operating Voltage: 3 tab, solder lug Nucl Timeria Type And Quantity: 3 tab, solder lug
 4.000 inches single mounting facility single center group Mounting Hole Diameter: 0.437 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Method: Flange single group and unthreaded hole single group Minding Operating Current: 25.00 aneytes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug N/a
Mounting Hole Diameter:0.437 inches single groupFrequency Rating:50.0 hertz single component and 60.0 hertz single componentInput-output Phase Relationship:Single phase to single phase single componentBody Length:10.438 inchesBody Width:9.688 inchesBody Height:4.812 inchesInclosure Type:Fully enclosedMounting Method:Flange single group and unthreaded hole single groupWinding Diameter:25.0 amperes ac single component single primary outputWinding Operating Voltage:120.00 ac volts single component single primary inputTerminal Type And Quantity:3 tab, solder lugNya
0.437 incles single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Minding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug N/a
Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Minding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug N/a
Input-output Phase Relationship: Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Mounting Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Minding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug N/a
Single phase to single phase single component Body Length: 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Mounting Method: Flange single group and unthreaded hole single group Minding Function And Quantity: 1 primary, variable autotransformer type single component Minding Operating Current: 25.0 amperes ac single component single primary output Minding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug N/a
Body Length:10.438 inchesBody Width:9.688 inchesBody Height:4.812 inchesInclosure Type:Fully enclosedMounting Facility Quantity:4 single groupMounting Method:Flange single group and unthreaded hole single groupWinding Function And Quantity:1 primary, variable autotransformer type single componentWinding Operating Current:25.0 amperes ac single component single primary outputWinding Operating Voltage:120.00 ac volts single component single primary inputTerminal Type And Quantity:3 tab, solder lugShelf Life:N/a
 10.438 inches Body Width: 9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Body Width:9.688 inchesBody Height:4.812 inchesInclosure Type:Fully enclosedMounting Facility Quantity:4 single groupMounting Method:Flange single group and unthreaded hole single groupWinding Function And Quantity:1 primary, variable autotransformer type single componentWinding Operating Current:25.0 amperes ac single component single primary outputWinding Operating Voltage:120.00 ac volts single component single primary inputTerminal Type And Quantity:3 tab, solder lugShelf Life:N/a
9.688 inches Body Height: 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Method: Flange single group and unthreaded hole single group Minding Method: 1 primary, variable autotransformer type single component Minding Operating Current: 25.0 amperes ac single component single primary output Minding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Body Height:4.812 inchesInclosure Type:Fully enclosedMounting Facility Quantity:4 single groupMounting Method:Flange single group and unthreaded hole single groupWinding Function And Quantity:1 primary, variable autotransformer type single componentWinding Operating Current:25.0 amperes ac single component single primary outputWinding Operating Voltage:120.00 ac volts single component single primary inputShelf Life:N/a
 4.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Inclosure Type:Fully enclosedMounting Facility Quantity:4 single groupMounting Method:Flange single group and unthreaded hole single groupWinding Function And Quantity:1 primary, variable autotransformer type single componentWinding Operating Current:25.0 amperes ac single component single primary outputWinding Operating Voltage:120.00 ac volts single component single primary inputTerminal Type And Quantity:3 tab, solder lugShelf Life:N/a
 Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
 Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Mounting Method:Flange single group and unthreaded hole single groupWinding Function And Quantity:1 primary, variable autotransformer type single componentWinding Operating Current:25.0 amperes ac single component single primary outputWinding Operating Voltage:120.00 ac volts single component single primary inputTerminal Type And Quantity:3 tab, solder lugShelf Life:N/a
 Flange single group and unthreaded hole single group Winding Function And Quantity: primary, variable autotransformer type single component Winding Operating Current: amperes ac single component single primary output Winding Operating Voltage: ac volts single component single primary input Terminal Type And Quantity: solder lug Shelf Life: N/a
 Winding Function And Quantity: 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
 1 primary, variable autotransformer type single component Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Winding Operating Current: 25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
25.0 amperes ac single component single primary output Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Winding Operating Voltage: 120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
120.00 ac volts single component single primary input Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
3 tab, solder lug Shelf Life: N/a
Shelf Life: N/a
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0