

View Online at <https://aerobasegroup.com/nsn/5950-01-023-5970>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

**Frequency Rating:**

380.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and brought out to terminal single component

**Body Length:**

Between 1.563 inches and 1.625 inches

**Body Width:**

Between 1.563 inches and 1.625 inches

**Body Height:**

Between 2.250 inches and 2.375 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

15.0 milliamperes ac single component 1st secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0