

View Online at <https://aerobasegroup.com/nsn/5950-01-023-5970>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

Between 1.563 inches and 1.625 inches

Body Width:

Between 1.563 inches and 1.625 inches

Body Height:

Between 2.250 inches and 2.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

15.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0