NSN 5950-01-023-6955

Audio Frequency Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-023-6955 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility single center group |
| Impedance Rating In Ohms: |
| 4.0 single component single secondary and 8.0 single component single secondary and 16.0 single component single secondary and |
| 500.0 single component single secondary |
| Frequency Rating: |
| 70.0 hertz single component and 20.0 kilohertz single component |
| Maximum Transformer Power Rating: |
| 25.0 watts single component |
| Primary To Secondary Turn Ratio: |
| 4.24 to 1 single component |
| Body Length: |
| 2.750 inches |
| Body Width: |
| 2.375 inches |
| Body Height: |
| 3.812 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 2 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 11 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 5950-01-023-6955

Audio Frequency Transformer - Page 2 of 2



Fiig:

A058b0