

View Online at <https://aerobasegroup.com/nsn/5950-01-024-3490>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration proof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.390 inches single mounting facility single center group and 1.410 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.190 inches single mounting facility single center group and 1.210 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

1.800 inches

Body Width:

1.645 inches

Body Height:

0.750 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

420.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

200.00 ac volts single component single primary

Special Features:

Each output terminal has an extra tap; terminals 16 through 27 are for hook up with a three phase bridge which is for testing purposes

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0