

View Online at <https://aerobasegroup.com/nsn/5950-01-025-1649>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.400 inches 2nd mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.780 inches 2nd mounting facility single center group

Mounting Slot Width:

0.218 inches 1st group

Frequency Rating:

57.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.590 inches

Body Width:

3.720 inches

Body Height:

4.340 inches

Distance Between Mounting Facility Centers:

3.075 inches 1st mounting facili type 2nd center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 3rd group

Mounting Method:

Threaded hole 3rd group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.190 inches 3rd group

Winding Operating Current:

2.5 amperes ac single component 4th secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Special Features:

Six secondaries

Thread Series Designator:

Unf 3rd group

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0