

View Online at <https://aerobasegroup.com/nsn/5950-01-025-3894>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches single mounting facility single center group

Impedance Rating In Ohms:

50.0 single component single primary

Frequency Rating:

3.0 kilohertz single component

Primary To Secondary Turn Ratio:

1 to 15 single component

Pulse Repetition Rate:

3.0 kilohertz single component

Body Length:

5.750 inches

Body Width:

5.500 inches

Body Height:

4.062 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

0.750 milliamperes ac single component single secondary

Test Data Document:

10001-2994344 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

4 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0