NSN 5950-01-025-5031

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-01-025-5031 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.438 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.155 inches single group and 0.162 inches single group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Transformer Winding Connection Type: |
| Delta-delta |
| Body Length: |
| 3.500 inches |
| Body Width: |
| 2.700 inches |
| Body Height: |
| 1.370 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Bracket single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 15.0 milliamperes ac single component single primary |
| Winding Operating Voltage: |
| 7.22 ac volts single component single secondary and 14.90 ac volts single component single secondary and 15.40 ac volts single |
| component single secondary and 23.50 ac volts single component single secondary and 25.30 ac volts single component single secondary |
| and 66.90 ac volts single component single secondary and 109.70 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 27 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A058b0