

View Online at <https://aerobasegroup.com/nsn/5950-01-025-9233>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration proof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.400 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.200 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

1.800 inches

Body Width:

1.645 inches

Body Height:

0.750 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

200.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

35.00 dc volts single component 1st secondary

Special Features:

Each output terminal has an extra tap; terminals 16 through 27 are for hook up with a three phase bridge which is for testing purposes

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0