

View Online at <https://aerobasegroup.com/nsn/5950-01-025-9665>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.312 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 4.930 inches and 5.060 inches

Body Width:

Between 4.180 inches and 4.310 inches

Body Height:

Between 5.310 inches and 5.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

350.0 milliamperes ac single component single primary

Winding Power Rating:

15.0 watts single component single primary

Winding Operating Voltage:

29.90 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0