NSN 5950-01-026-1624

Radio Frequency Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-026-1624

Coll Form Type: Solid single component Body Length: 0.250 inches Body Outside Diameter: 0.095 inches Body Outside Diameter: 0.095 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding De Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 181349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Sheft Life: N/a Unit Of Measure:	
Coli Form Type: Solid single component Body Length: 0.250 inches Body Outside Diameter: 0.095 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating in Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inductance Rating:
Solid single component Body Length: 0.250 inches Body Outside Diameter: 0.095 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating in Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	0.22 microhenries single component single winding
Body Length: 0.250 inches Body Outside Diameter: 0.095 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Coil Form Type:
Body Outside Diameter: 0.095 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Solid single component
Body Outside Diameter: 0.095 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	0.250 inches
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Outside Diameter:
Fully enclosed Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	0.095 inches
Mounting Method: Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Type:
Terminal single group Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Fully enclosed
Winding Operating Current: 1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Method:
1025.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: —— Demilitarization: No Fiig:	Terminal single group
Dc Resistance Rating In Ohms: 0.140 single component single winding Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Winding Operating Current:
Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	1025.0 milliamperes dc single component single winding
Quality Factor: 33 single component single winding Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Dc Resistance Rating In Ohms:
Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.140 single component single winding
Test Data Document: 81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Quality Factor:
81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	33 single component single winding
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 wire lead
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A058b0	Fiig:
	A058b0