NSN 5950-01-026-5158

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-026-5158
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.703 inches single mounting facility single center group and 3.797 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.953 inches single mounting facility single center group and 3.047 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
5.500 inches
Body Width:
4.500 inches
Body Height:
6.750 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 3 secondary single component
Thready Qty Per Inch (tpi):
20 single group
Thread Size:
0.250 inches single group
Winding Operating Current:
410.0 milliamperes ac single component 2nd secondary
Winding Operating Voltage:
662.00 ac volts single component 2nd secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5950-01-026-5158

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0