## NSN 5950-01-026-5964

Pulse Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-026-5964

Reliability Indicator:  Not established  Center To Center Distance Between Mounting Facilities Parallel To Length:  1.000 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width:  0.875 inches single mounting facility single center group  Pulse Repetition Rate:  35.0 kilohertz single component  Body Length:
Center To Center Distance Between Mounting Facilities Parallel To Length:  1.000 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width:  0.875 inches single mounting facility single center group  Pulse Repetition Rate:  35.0 kilohertz single component
1.000 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width:  0.875 inches single mounting facility single center group  Pulse Repetition Rate:  35.0 kilohertz single component
Center To Center Distance Between Mounting Facilities Parallel To Width:  0.875 inches single mounting facility single center group  Pulse Repetition Rate:  35.0 kilohertz single component
0.875 inches single mounting facility single center group  Pulse Repetition Rate:  35.0 kilohertz single component
Pulse Repetition Rate: 35.0 kilohertz single component
35.0 kilohertz single component
Body Length:
Dody Longin.
1.375 inches
Body Width:
1.250 inches
Body Height:
1.875 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Bracket single group and threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thread Size:
0.138 inches single group
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A058b0