

View Online at <https://aerobasegroup.com/nsn/5950-01-026-5970>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 0.390 inches and 0.430 inches

**Inductance Rating:**

0.22 microhenries single component single winding

**Coil Form Type:**

Solid single component

**Core Construction:**

Solid single component

**Overall Diameter:**

Between 0.152 inches and 0.172 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Rating Method:**

Electrical single component single winding

**Features Provided:**

Tinned wire leads

**Winding Operating Current:**

1.1 amperes dc single component single winding

**Dc Resistance Rating In Ohms:**

0.067 single component single winding

**Quality Factor:**

49 single component single winding

**Special Features:**

Suffix letter on p/n 15s-r22k denotes a standard tolerance of 10 pct

**Test Data Document:**

81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 wire lead

**Specification Data:**

96906-ms75087 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0