

View Online at <https://aerobasegroup.com/nsn/5950-01-026-7713>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

30.0 watts single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.063 inches

Body Width:

2.880 inches

Body Height:

2.563 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.0 amperes dc single component single secondary

Winding Power Rating:

38.4 volts-amperes single component single secondary

Winding Operating Voltage:

19.20 ac volts single component single secondary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0